



GULFTEC[®] FULL SYNTHETIC HIGH MILEAGE MOTOR OIL

Specially designed for high-mileage vehicles

Synthetic base oils uniquely engineered to provide added engine protection for high mileage, gasoline powered engines or vehicles of any age. Protects new vehicle warranties where fully licensed API Service Category SP and ILSAC GF-6A oils are required. Proven to reduce high temperature varnish deposits, ring sticking and an excellent choice for use in all seasons. A balance of effective additives that maintain the condition of seals and gaskets that helps control leaks and oil consumption, particularly during severe driving conditions.

Features and Benefits

- Provides extra wear protection
- Excellent low-temperature pumpability
- Provides extra cleaning to critical engine parts
- Condition seals and makes them less susceptible to leaking

Approvals

- API SP / ILSAC GF-6A
- Previous API "S" categories including SN Plus, SN, and SM

Applications

- Lower mileage vehicles, including new cars still under warranty
- Older mileage and rebuilt passenger cars, light duty trucks and SUVs

Typical Properties

SAE Grade		0W-20	5W-20	5W-30	10W-30
Product Code	Test Method	330360	330362	330364	330366
Gravity, API	ASTM D-4052	35.8	32.8	33.0	31.0
Kinematic Viscosity, cSt at 40°C	ASTM D-445	44.5	52.0	62.0	68.0
Kinematic Viscosity, cSt at 100°C	ASTM D-445	8.4	8.8	10.5	10.6
Viscosity Index, calculated		171	153	158	143
Pour Point °F	ASTM D-97	-45	-43	-40	-35
Cold Cranking at temp °C, cP	ASTM D-5293	5200 @ -35	5400 @ -30	4800 @ -30	5500 @ -25
Color	ASTM D-1500	3.0	3.0	3.5	3.5
Flash Point (COC) °F	ASTM D-92	440	440	450	460
Chrysler MS-6395			Yes	Yes	Yes
Ford WSS-		M2C962-A1	M2C960-A1	M2C961-A1	

Note: Minor variations in product are to be expected in normal manufacturing. Always confirm with the original manufacturer's recommendation for proper equipment operating requirements.

(∰)

Rev. 7/23





