



LUBRICANTS



Product Data Sheet

VP Preservative Oil 100

Vapor Phase Corrosion Inhibiting Properties

Specialized circulating and lubricating oil that exhibits outstanding rust protection. It is formulated to provide rust protection on the internal surfaces of machinery which come in contact with the oil, leaving a thin film. The residual film provides an effective medium-term protection barrier against corrosion during intermediate storage or transportation. Its unique design also provides a rust inhibitor vapor for steel surfaces which are above the level of the oil in an enclosed space. Draining and flushing of the treated system with the recommended OEM lubricant is suggested to remove VP Preservative film.

Features and Benefits

- Effective Anti-Wear Properties
- Leaves a Thin Film After Oil is Drained
- Excellent Rust and Corrosion Protection
- Extended Rust Protection for Metal Surfaces Submerged in Oil

Applications

- Engines
- Gear boxes
- Closed systems

Typical Properties

Product Code	Test Method	335388
Kinematic Viscosity, cSt @40°C	ASTM D 445	91.5
Kinematic Viscosity, cSt @100°C	ASTM D 445	10.8
Viscosity Index	ASTM D 2270	100
Flash Point, COC, °F	ASTM D 92	442
Specific Gravity	ASTM D 129	0.865
Rust Test, Synthetic Sea Water	ASTM D 665	Pass
Rust Test, Distilled Water	ASTM D 665	Pass
Copper Corrosion, 3 hrs. @ 212°F	ASTM D 130	1B

These properties are typical of current production, minor variations are to be expected in normal manufacturing.

Rev. 01/24



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

