



LUBRICANTS



Product Bulletin

Gulfpride® Two Cycle Marine Engine Oil

Two-Stroke Engine Oil

Ashless, two-stroke (cycle) engine oil formulated with high-quality base oils and an ashless high temperature additive system designed to control deposits and protect engine parts from corrosion and wear.

Features and Benefits

- Blue tint for easy identification
- Reduces carbon and deposit build-up on engine parts
- Helps prevent piston and ring sticking
- Resists the formation of harmful gels and deposits during temporary storage

Applications

- Direct inject and pre-mix systems
- Outboard Marine Corporation (Johnson / Evinrude), Mercury, Chrysler, Kawasaki, Yamaha, and Suzuki, as well as other outboard marine engine manufacturers

Typical Properties

Product Code	Test Method	330501
Kinematic Viscosity, cSt at 40°C	ASTM D-445	56.3
Kinematic Viscosity, cSt at 100°C	ASTM D-445	9.1
Brookfield Viscosity @ -25°C, cP	ASTM D-2983	4,300
Sulfated Ash, Mass %	ASTM D-874	Nil
Pour Point	ASTM D-5949	-33°F
Color	Visual	Blue
Flash Point, (PM) °F	ASTM D-93	219°F

Rev. 08/26



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

